




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 11/04		A1	(11) International Publication Number: WO 96/23391
			(43) International Publication Date: 1 August 1996 (01.08.96)
(21) International Application Number: PCT/EP95/00276 (22) International Filing Date: 26 January 1995 (26.01.95) (71) Applicant (for all designated States except US): INTERNATIONAL BUSINESS MACHINES CORPORATION [US/US]; Old Orchard Road, Armonk, NY 10504 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): LUIJTEN, Ronald, Peter [NL/CH]; Alte Landstrasse 150, CH-8800 Thalwil (CH). WEBB, David, John [US/CH]; Muehlestrasse 4, CH-8803 Rüschlikon (CH). (74) Agent: BARTH, Carl, Otto; International Business Machines Corporation, Säumerstrasse 4, CH-8803 Rüschlikon (CH).		(81) Designated States: BR, CA, CN, JP, KR, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: METHOD AND APPARATUS FOR ATM SWITCHING



(57) Abstract

A switch for use in an ATM network is disclosed. The switch is designed to perform a function beyond that normally achievable with a virtual path switch functioning in accordance with the ATM standard. The switch according to the invention has data stored in a look-up table (431-433) which allows it to identify communication cells of particular individual virtual channels, indicated by the virtual path identifier (VCI), although these cells cannot be distinguished on the basis of their virtual path indicators (VPIs). This identification is attempted before the usual step of forwarding an incoming communication cell based solely on its virtual path indicator. A priority circuitry (44) ensures that entries associated with the combined VPI/VCI is given a priority over those associated only with the VPI. The switch can extract cells of individual virtual channels passing through it. It can also insert virtual channels into the ATM network.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

DESCRIPTION

Method and Apparatus for ATM Switching

An Asynchronous Transfer Mode (henceforth ATM) network has switching points within the network. The "switching" performed by these switching points is in fact the action of passing on a communication received by that switching point to a further link in the network. Such switching actions are the means by which a communication is moved through the ATM network. The method and apparatus of the invention relate to a way of performing one type of switching operation at a switching point in an ATM network.

BACKGROUND OF THE INVENTION

The ATM system has a broadly accepted set of standards which ensure compatibility of ATM networks and their components. The book "ATM (broadband-ISDN) a technical overview", published as publication GG24-4330-00, can be consulted in order to gain familiarity with the ATM system.

The ATM standards define the following basic characteristics of ATM communication:

- All digital information is converted into cells (henceforth simply "cells"). These cells are transferred via a transmission medium.

- Each cell has a fixed data length. The cell consists of a 5-byte header and a 48-byte information field. One part of the header carries data which is termed a "Virtual Path Identifier" (henceforth the "VPI"). Another part of the header carries data termed a "Virtual Channel Identifier" (henceforth the "VCI").

1 Figure 1 (prior art) illustrates the parts of the header recognised as belonging to the VPI and VCI. At certain points in the ATM network, the region of the header labelled "GFC" (Generic Flow Control) is also interpreted as part of the VPI.

5

- The path to be followed by a cell through an ATM network is defined by a series of "look-up tables" which are prepositioned in the switching points of the network. These look-up tables contain routing information to be consulted when a cell arrives at the switch point.

10

- The ATM network has some switching points called "Virtual Channel Switches". A "Virtual Channel Link" is the link between two successive virtual channel switches in the ATM network. A "Virtual Channel Connection" (VCC) is a route through the ATM network consisting of a particular set of virtual channel links. An example of such a virtual channel connection is the route from the point of origin of a communication in the ATM network via two or more virtual channel links to the destination of the communication in the ATM network. It should be clearly understood that the virtual channel "connection" here refers to a route through the ATM network and not to the action of making a connection.

20

A switching action performed at a virtual channel switch in the ATM network is made in dependence on the data in both the VPI and VCI fields of the cell's header.

25

- The ATM network also has some switching points called "Virtual Path Switches". A "Virtual Path Link" is the link between two successive virtual path switches in the ATM network. There may be several virtual path switches within one virtual channel link. The "Virtual Path Connection" (VPC) is the route through several virtual path switches followed by a particular cell. A switching action performed at a virtual path switch in the ATM network is made in dependence on only the data in the VPI field of the cell's header. In short, a VPI bundles several VCIs.

30

1 The prior art figure 2 illustrates the differences in the VP and the VC switching using a layer model. The lowest level of the model consists of the physical layer, i.e., the layer on which signals are exchanged. The virtual path connection layer (ATM VP) can be regarded as being mounted on the physical layer. A virtual path connection is marked VPC. The virtual channel connection layer (ATM VC) can be seen as third layer. A virtual channel connection is marked VCC. The origin of the cells in the simplified network of figure 2 is marked ORIG and their destination DEST. Figure 2 recalls that virtual channel switching and virtual path switching are separate layers in the ATM hierarchy, even though some switches may act as either virtual channel or virtual path switch. However, the standard operation of a VC/VP foresees no means to cross from the VPC layer to the VCC layer except by terminating the entire VP and redirecting all VCs contained in it.

15 It may be equally instructive for an accurate understanding of the current invention to review the function of the look-up tables stored at the switching points:

A cell starts at its entry point into the ATM network with a certain value stored in the VPI data field in its header. When the cell reaches the first virtual path switch, this switch reads the VPI in the header. The value of the VPI is now used either directly or indirectly to derive the address to be located in the look-up table held in the virtual path switch. The data value found at that particular address in the look-up table is then put into the cell's header in place of the original VPI. The particular exit port from the virtual path switch out of which the cell is to be sent is also determined by a value stored at the same address in the look-up table. The cell is now sent from the first virtual path switch further through the ATM network, having had its VPI value changed by the virtual path switch. At each subsequent virtual path switch in the virtual path connection a similar switching action to this takes place, i.e. the value of the VPI in the cell on arrival at the switch is accessed in the look-up table, and the value stored in the look-up table under that address is inserted into the VPI data field in the cell's header

- 1 prior to sending the cell further through the network. Thus the values stored in the look-up tables at the various switching points determine the cell's route through the ATM network.
- 5 Although the VPI value can be used as the address in the look-up table, other arrangements for finding a particular entry in the table may be contemplated. It is only important that the VPI value of the incoming cell reliably leads to the location of the stored information which tells the virtual path switch how to direct that cell. In particular, an example shown later in
- 10 the description splits the look-up table described above into separate tables, to be used one after the other.

By definition, all cells having the same VPI are switched together at a virtual path switch, i.e. they are all sent on with the same new VPI independently of

15 their VCI value. Therefore several cells with different values of VCI may follow the same virtual path connection. Thus the virtual path connection can be considered to be effectively a bundle of virtual channel connections.

In general, there will be one particular look-up table in the virtual path switch for each input port to the switch. Therefore a cell arriving at the switch at one particular input port with one particular VPI value in its header will not necessarily be sent out on the same output port as a cell with the same VPI value which arrives at the same virtual path switch on a different input port.

25

The switching action performed at a virtual channel switch involves consulting a look-up table which has entries accessed according to the value of the VPI and VCI data fields together. Comparing the possible number of VP addresses and of VC addresses, it is obvious that a VC switch

30 requires larger look-up tables and thus vastly more memory capacity. In practice, a VC switch requires about thousand times more memory space than a VP switch in the same network.

1 There is in fact nothing in the ATM standard which prevents one switching
point in the ATM network acting as both a virtual path switch and a virtual
channel switch. Such dual function nodes in the ATM network fall within the
scope of the present invention. For simplicity of explanation however, this
5 description will deal only with switches which serve one of these functions.

The ATM standards for the VPI and VCI are given in "CCITT
Recommendations I. 361 and 363".

10 ATM switching technology is also disclosed in numerous patents and patent
applications. US Patent 5 239 537 for example describes means and
methods to substitute a corrupted VP by an alternate VP. The US Patent
5 271 010 to Miyake describes a converter for converting the VPI and a VCI,
i.e., the full 28 bit address attached to the header of an ATM cell. The
15 converter comprises a plurality of identifier comparator units and a
controller. Each of the identifier comparator units has an input identifier
memory for storing an identifier attached to an ATM cell and a comparator
for comparing the identifiers of an incoming ATM cell with the identifiers
stored in the input identifier memory.

20 In view of the known ATM standard and technology, it is seen as object of
the invention to provide means for selectively accessing cells having the
same VPI but different VCIs. More particular, the invention aims at providing
a method and a device for adding and dropping cells with a particular VCI
25 from a VPI stream at a VP switch without having to terminate the VPI for all
cells at this VP switch.

SUMMARY OF THE INVENTION

30 The above-mentioned objects are achieved by methods and devices having
features and elements as set forth in the appended claims.

1 A virtual path switch in a network according to the ATM standard is envisaged as carrying out the switching action described above, i.e. consulting the address in its look-up table which corresponds to the VPI of the incoming cell, and sending on the cell at an output and with a new VPI
5 which have been retrieved from that address in the look-up table.

The present invention gives the virtual path switch the capability of performing an additional form of switching. This switching involves extracting one or more particular virtual channel connections from the
10 virtual path connections being routed through the switch. This extraction is, in other words, a "breaking out" or "dropping out" of one or more virtual channel connections from a VP connection. The method and apparatus according to the invention achieve this extraction with a minimum of additional memory capacity in the switch's look-up table. Thus the invention
15 requires relatively little additional memory capacity and expense in the virtual path switch in comparison to less efficient methods of performing this breaking out operation.

The following features may be regarded as being characteristic to the
20 invention.

A conventional VP switch usually contains memory means for storing a look-up table for addresses for all the VPI headers of cells which are to be switched onto another virtual path link towards another virtual path switch.
25 It is further assumed that the switch contains a look-up table for addresses based on the combined VPI and VCI values of incoming cells. In the look-up table for the VCI/VPI, the addresses of those one or more virtual channels which are to be extracted at that virtual path switch are stored. For the purpose of the invention, it is not important whether these look-up tables are
30 stored in a common or in separate memories. It is further of no importance whether the look-up table for the VPI is part of the look-up table for the combined VCI/VPI look-up or implemented separately, whereby a higher switching speed can be achieved.

1 When a cell is received at the virtual path switch, both its VPI and VCI value are examined. An attempt is first made to find a corresponding address in the look-up table for VPIs and VCIs. If this attempt is successful, then this cell must belong to one of the virtual channels which is to be switched as
5 VCs at that virtual path switch. i.e. , this channel is extracted and forwarded through the ATM network after replacing in accordance with the entries in the look-up table the old VCI/VPI header by a new one. If the attempt is unsuccessful then the cell's VPI value alone is looked up in the look-up table. The cell is then forwarded through the ATM network with the new VPI
10 value and from the output terminal of the virtual path switch which was indicated at the address in the look-up table. The invention provides in other words a priority for entries to the combined look-up table over entries of the VPI look-up table.

15 The simplicity and advantage of this arrangement is that the look-up table need only contain one extra entry per virtual channel to be extracted. The arrangement of the present invention involves far less memory than the prior art method of breaking out individual virtual channels at a virtual path switch, where the entire virtual path has to be divided into all its individual
20 virtual channels, and those virtual channels which are not to be broken out at that virtual path switch are then re-bundled into a new virtual path and sent on through the ATM network. This known method requires that the VCI values of all the virtual channels of the "terminated" VP are stored in the look-up table. The invention modifies a VP switch such that it can be used
25 as VC switch without having the full look-up table of all VPI and VCI addresses used by virtual channel switches to perform their analogous function.

In a further aspect, the invention encompasses a method and apparatus for
30 introducing or "adding" a virtual channel into a virtual path passing through a virtual path switch. This action can be seen as being the opposite of the above described extraction of a virtual connection from a virtual path. The combination of both aspects of the invention thus provides a complete

1 ADD/DROP for ATM cells passing through a VP switch. The details of the
method and apparatus for adding the virtual channel connection will
become apparent from the detailed embodiment of the invention described
below in connection with the figures.

5

These aspects, as well a preferred mode of use, and further objects and
advantageous thereof, will best be understood by reference to the following
detailed description of illustrative embodiments when read in conjunction
with the accompanying drawings.

10

DESCRIPTION OF THE DRAWINGS

The invention is described in detail below with reference to the following
15 drawings:

FIG. 1 shows a simplified diagram of the header of an ATM cell
according to the ATM standard;

20 **Fig. 2** shows virtual path switches and connections together with
virtual channel switches and connections according to the ATM
standard;

Figs. 3A-3C show look-up tables and a database stored at a virtual path
25 switch in accordance with the invention;

Fig. 4 shows basic elements of an embodiment in accordance with the
present invention.

30

MODE(S) FOR CARRYING OUT THE INVENTION

Referring to Figures 3A-3C, a set of tables and a database is shown which
5 could be stored in a switch in accordance with the present invention. These
tables have been simplified, e.g. by having addresses with fewer digits than
is the case in an actual ATM network.

Figure 3A shows a look-up table which is accessed using the virtual path
10 indicator (VPI) together with the virtual channel indicator (VCI) of a cell. This
is henceforth referred to as the "VPI/VCI" table. This VPI/VCI table is not
foreseen by the ATM standard for inclusion in the virtual path switches of an
ATM network.

15 In accordance with this embodiment of the invention, the VPI/VCI table
contains as many entries as there are individual virtual channels which
must be extracted from the ATM network at this virtual path switch. In the
example shown there are two virtual channels which must be extracted- the
channel whose cells have a value of 001 as their VPI and 004 as their VCI,
20 and the channel with a VPI of 001 and VCI of 006. For simplification, the
address used in the table has been shown as the combination of the VPI
and VCI into a single six digit number. Many alternative combination
schemes of the VPI and VCI numbers could however be used.

25 The index number held under each address of the VPI/VCI table can take
any form. This number is merely a pointer or address to a location in the
database shown in figure 3C.

Figure 3B shows a look-up table which is accessed using only the virtual
30 path indicator (VPI) of a cell. This table is henceforth referred to as the "VPI"
look-up table. This table can be viewed as contributing to the function of a
virtual path switch as foreseen by the ATM standard. It contains entries for
the VPI values of all the virtual paths passing through the network. In the

1 present case, it is assumed that there are five virtual paths which pass
through the virtual path switch, and they have been numbered 001 to 005.
Note that there may be many individual virtual channels with just one of
these VPI values. This is however not of importance in the decision of how
5 to direct these channels onwards through the network if they are not to be
extracted at the switch. Therefore table 3B does not contain any VCI
numbers in its indexing scheme. The VPI table shown in figure 3B has
under each address an index number which refers to an address in the
database of figure 3C.

10

Figure 3C shows a database. This database contains the associated
information or instructions for handling a cell received by the virtual path
switch. The associated information are accessed using as addresses the
index numbers which were found in either table 3A or table 3B. The
15 associated information in the table have been simplified as to containing
new VPI and VCI values as well as information concerning the output port of
the switch for cells which are to be sent on further through the ATM
network. Usually for those VCI appearing in the table of Fig. 3A, i.e., the
virtual channels marked for dropping, new VCI/VPI are provided and the
20 affected cells are sent on further through the ATM net. The invention
however contemplates using other instructions than those necessary for
passing on the cells to another node within the ATM network. These
instructions are labeled by "(EXTRACT)" in the database of Fig. 3C. These
values are available for cells which belong to virtual channels which are to
25 be extracted at the virtual path switch. The exact form of this would depend
on what is to be done with the virtual channel. The cells of the extracted
virtual channel may for example simply be used locally.

Figure 4 shows an embodiment of the apparatus according to the invention
30 in operation. Memory blocks 431-433 are shown to store the tables
discussed above in connection with figure 3. The combined VCI/VPI table is
preferably implemented as associative memory, which facilitates the
handling of a comparatively small selection from a vast number of possible

1 entries. The apparatus comprises portions 41, 42 for extracting and
inserting the header of cells into the data stream carried by a cell data bus
40. These portions as the memory means are in principle known. The
invention adds means 44 which effectively give -in case that an entry is
5 found in both look-up tables 431, 432 - priority to the index found in the
combined VCI/VPI table 431. The priority circuitry 44 can easily be
implemented by suitable logical gates, latches, and/or programmable
devices. In the described embodiment, a gate 440 controls the latch 441
such that the index of table 431 addresses the database 433 when the entry
10 found lines EF1, EF2 are both high. The exact truth table of the priority
circuitry 44 is:

	EF1	EF2	OUT
15	0	0	x
	1	0	I1
	0	1	I2
20	1	1	I1

Quite clearly the embodiment explained above in connection with figures 3
and 4 only shows one variant of the present invention. In particular, the
25 exact allocation of the information held amongst the tables and database
can be varied. It is however important that the switch contain information
allowing it to recognise an incoming cell of a virtual channel which is to be
extracted, on the basis of the VPI and VCI data values in the cell's header. It
is also important that only for these cells does both VPI and VCI data need
30 to be held in the switch. This contrasts with the data requirements of both
virtual path switches and virtual channel switches known from the prior art.
The sequence of steps employed to compare the VPI and VCI values with
the values held in the tables and database can also be varied.

1 The arrangement of the invention explained in connection with figures 3 and
4 shows an extraction of virtual channels from an ATM network. The
invention is however equally capable of inserting one or more virtual
channels into an ATM network. This embodiment of the invention would for
5 example be useful when a local source wishes to insert a virtual channel at
the location of a virtual path switch, or when it is desired to "splice in" a
connection from another ATM network at the site of a virtual path switch.

10 In order to insert a virtual channel into an ATM network, it is necessary to
provide the header of each cell of that virtual channel with VPI and VCI
values for its passage through the ATM network, and to feed it into the ATM
network through the appropriate output port of the virtual path switch. All of
this information can be stored in a database of the form of that shown in
figure 3C. Access to the database needs to be via a look-up table which
15 yields index numbers in a manner similar to that of the table in figure 3A,
but which is indexed by the existing VPI and VCI values of the virtual
channels to be added to the network, or some similar identifying parameter.

20

25

30

CLAIMS

- 1
1. An Asynchronous Transfer Mode (ATM) switching apparatus comprising
memory means (431-433) for storing look-up tables for Virtual Path
5 Identifiers (VPIs) and Virtual Channel Identifiers (VCIs), said identifiers
being part of the header information of a ATM cell, and for storing
information associated to said VPIs and VCIs,
said apparatus being characterized by
- means for performing either simultaneously or sequentially a look-up
10 operation with the combined VCI/VPI and a look-up operation with only
the VPI of an incoming ATM cell, and
 - priority means (44) for giving entries found in said look-up operation
with the combined VCI/VPI a priority over entries found in said look-up
operation with only the VPI.
- 15
2. The apparatus of claim 1 where the function of the memory means is
divided between
- means for storing a first look-up table (431), which yields an
index-number and is addressed by using the virtual path indicator and
20 virtual channel indicator of a cell together; and
 - means for storing a second look-up table (432), which yields an index
number and is addressed by using only the virtual path indicator of a
cell;
 - and means for storing a database (433), which is addressed using an
25 index number obtained from either the first or second look-up table and
which stores at each address the instructions to be used on receipt of a
communication cell of either a particular virtual path or a particular
virtual channel.
- 30
3. For an ATM switching apparatus, a method allowing the breaking of one
or more individual virtual channels (VCs) out of a single virtual path
(VP),
comprising the steps of

- 1 a) deriving and storing an entry in the look-up table located in the said
particular switch for each of the said individual virtual channels whose
cells are to be selectively processed at that switch, these entries being
accessible using both the virtual path identifier and the virtual channel
5 identifier of cells of the said individual virtual channels;
- b) when a communication cell is received by the switch, seeking an
entry in the look-up table which corresponds to both the virtual path
identifier and the virtual channel identifier of that cell, and if such an
entry is found, processing the cell according to the information found
10 under that entry;
- c) otherwise, routing the cell onwards through the ATM network in
accordance with the information stored in the look-up table under the
entry which corresponds to the virtual path identifier of the cell.



15

20

25

30

1/3

*Fig. 1 (Prior art)**Fig. 2 (Prior art)*

2/3

ADDRESS (VPI/VCI)	INDEX
001 004	1000
001 006	1001
•	•
•	•
•	•


Fig. 3A

ADDRESS (VPI)	INDEX
001	0001
002	0002
003	0003
004	0004
005	0005
•	•
•	•
•	•

Fig. 3B

INDEX	ACTION			
	VPI (new)	VCI (new)	Output port	Other
0001	101	—	1	—
0002	102	—	1	—
0003	103	—	2	—
0004	104	—	2	—
0005	105	—	2	—
•				
•				
•				
1000	003	001	2	—
1001		(EXTRACT)		
•				
•				

Fig. 3C

*Fig. 4*

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/EP 95/00276

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04Q11/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	IEEE COMMUNICATIONS MAGAZINE, vol. 32, no. 8, 1 August 1994 pages 52-59, XP 000471042 CHAO H J ET AL 'IP ON ATM LOCAL AREA NETWORKS' see page 53, left column, line 20 - right column, line 30; figures 2,7 see page 57, right column, line 20 - page 59, left column, line 18; figure 2 ---	1-3
A	ONVURAL R O 'ASYNCHRONOUS TRANSFER MODE NETWORKS: Performance Issues' 1994, ARTECH HOUSE, NORWOOD MA 21228 see page 191, line 3 - page 194, line 25; figures 6.1-6.4 -----	1-3

☐ Further documents are listed in the continuation of box C.☐ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

26 September 1995

Date of mailing of the international search report

06.10.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Veen, G